

Available Function For MC-5438

Function		Out1	Out2	Alarm	Remote SV	CT Input	DC 24V Supply	Communication	Power Input DC 24V
Model No.		B	C	D	F		EXTRA FUNCTIONS	G	EXTRA FUNCTIONS
MC-5438 (A) 48 x 48 mm DIN 1/16	1.	Relay 1C	None	1-2 set	Pick 1 among the 3			V (RS485 or RS232) <remark 1> <remark 2>	V (with main 24VDC supply)
		Relay 1A							
		24V Pulsed							
		4~20 mA							
		1~5V							
		0~5V							
		0~10V							
		1~5V							
	2.	Motor Valve	None	1-2 set	None	None	None		
	3.	Relay 1A	Relay 1A	1-2 set	None	None	None		
		24V Pulsed	24V Pulsed						
		4~20 mA	4~20 mA						
		0~5V	0~5V						
		0~10V	0~10V						
		1~5V	1~5V						
		2~10V	2~10V						
	4.	Out 1	Transmitter	Alarm	Remote SV	CT Input	DC 24V Supply		
		B	E	D	F		EXTRA FUNCTIONS		
		Relay 1A	4~20mA	1-2 set	None	None	None		
		24V Pulsed	0~20mA						
		4~20 mA	0~5V						
		0~5V	0~10V						
		0~10V	1~5V						
		1~5V	2~10V						
		2~10V							

P.S:

(1). For all type →

Out 2 or motor valve is not available for program function.

(2). For MC-5438 →

Remark 1. Alarm2 and RS232 (select only one function).

Remark 2. With extra DC 24V : RS485/RS232 or Out 2 (select only one function).

※External terminal :

