



TMPT



S. C. R. Unit

(3 Fuse use)

TMPT								Model No.
0304L	0504L	0804L	1004L	1204L	1604	2004	2504	3004
								Dimensions (Unit: mm)
								Load Current Rating (A)
100~500V								Load Voltage (V)
Operating: 0~50°C, Storage: -10~70°C								To Take Pressure Ambient Temp.
0~90%								RH
88~264V (50Hz / 60Hz)								Auxiliary Power
0.6A								Min Load Current
8mA (R.C Filter)								Off State Leakage Current
3.2W (Max.)								Power Consumption
50Hz / 60Hz								Frequency Range
•								Control Type (Input)
•								
•								
•								
•								
DCA (250Ω) / DCA (4.7Ω or 10kΩ)								Input Resistance
AC 2000V (1 min input & output to ground)								Isolation Voltage
—								Alarm
3 phase 3 fuses								Notation
Approx. 1800	Approx. 2200	Approx. 3475	Approx. 5400	Approx. 9400	Approx. 16500	Net Weight (g) (Include heat sink)		
<ol style="list-style-type: none"> <li>Phase angle control, 3 phase with 3 fuses.</li> <li>Fuse included.</li> <li>Good accuracy with digit control.</li> <li>With self-diagnosis function (phase fail and fuse open)</li> <li>Auxiliary power supply is necessary for control.</li> <li>Input signal can be ordered with 0~20mA / 4~20mA / 0~5V / 1~5V / 0~10V DC.</li> </ol>								Features

T  
M  
P  
T