



MP3S



S. C. R. Unit

(3 Fuse use)

Model No.	MP3S										
	0304L	0504L	0704L	1004L	1204L	1504	1604	2004	2254	2504	3004
Dimensions (Unit: mm)											
Load Current Rating (A)	30A	50A	70A	100A	120A	150A	160A	200A	225A	250A	300A
Load Voltage (V)	100~500V										
To Take Pressure	—										
Ambient Temp.	Operating: 0~50°C, Storage: -10~70°C										
RH	0~90%										
Auxiliary Power	—										
Min Load Current	0.6A										
Off State Leakage Current	—										
Power Consumption	—										
Frequency Range	50 Hz / 60 Hz										
Control Type (Input)	0~20mA	—									
	4~20mA	•									
	0~5V	—									
	1~5V	—									
	0~10V	—									
2~10V	—										
Input Resistance	—										
Isolation Voltage	AC 2000V (1 min input & output to ground)										
Alarm	—										
Notation	3 phase 3 fuses										
Net Weight (g) (Include heat sink)	Approx. 1800	Approx. 2200	Approx. 3475	Approx. 5400	Approx. 5500	Approx. 6000	Approx. 6500	Approx. 7200	Approx. 9000	Approx. 9000	Approx. 9000
Features	1. Phase angle control, 3 phase with 3 fuses. 2. Fuse included. 3. High accuracy with analog control, and multi alarm output. 4. 4~20mA can drive thyristor directly, Auxiliary power supply is not necessary to make easy wire connection and maintenance. 5. Input signal 4~20mA available only. 6. CE Approval										

MP3S